

Energy meters



Conto D2-b

Single-phase I.v. network
Direct connection current 36A
Direct connection voltage 230-240V
Active energy cl.1
2 module housing



Conto D2

▶▶ Single-phase I.v. network
Direct connection current 36A e 63A
Direct connection voltage 230-240V
Total and partial active energy cl.1
Current, voltage, active power
Pulse output (option)
2 module housing



Conto D4-Pt

▶▶ Single-phase and three-phase I.v./M.V. network
Current CT/1A and /5A (same model) programmable ratio
▶ Direct connection voltage up to 440V (phase-phase) or on VT programmable ratio
Total and partial active energy cl.1
Total and partial reactive energy cl.2
Power demand and max. power demand
Pulse output (kWh or kvarh) and/or RS485 communication (option)
4 module sealable housing



Conto D4-Pd

▶▶ Three-phase I.v. network
Direct connection current 63A
▶ Direct connection voltage up to 440V (phase-phase)
▶ **Active energy cl.1: total and partial or double tariff**
Reactive energy cl.2: total and partial or double tariff
Power demand and max. power demand
Pulse output (kWh or kvarh) or RS485 communication (option)
4 module sealable housing



Conto 72-Pt



Conto 96-Pt

▶▶ Single-phase and three-phase I.v./M.V. network
Current CT/1A and /5A (same model) programmable ratio
▶ Direct connection voltage up to 440V (phase-phase) or on VT programmable ratio
▶ **Total and partial active energy cl.1**
Total and partial reactive energy cl.2
Power demand and max. power demand
Pulse output (kWh or kvarh) or communication RS485
Flush mounting housing, 72x72mm (Conto 72-Pt) front frame and 96x96mm (Conto 96-Pt) front frame



**PULSE
OUTPUT**



COMMUNICATION